




- Main Extrusion: 2" Square, 1/8" Wall with 1/8" Radius Corners, 6063 T6 Aluminum
- Joint Sleeve: 1.75" Square, 1/8" Wall with 1/8" Radius Corners, 6063 T6 Aluminum
- Ground Support: 2" x 0.5", 1/8" Wall, 6063 T6 Aluminum
- Unique Chevron Interlocking System Between Sections
- Straight and Radius Sections Measure Twenty Feet (20') in Length and Are Numbered for Ease of Installation
- Form Fitted and Manufactured to Exact Track Specifications From Provided Project Layout Drawings and Striping Plan Information, *REQUIRED BY OTHERS
- Curbing Sits 1/2" Above Synthetic Track Surface on Ground Supports For Efficient Drainage
- Natural Mill Finish
- Meets World Athletics, NCAA, and USATF Specifications, Rules, and Requirements
- Non-Permanent Installation

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SPORTSFIELD SPECIALTIES INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SPORTSFIELD SPECIALTIES INC. IS PROHIBITED.

TCBM Mill Finish Aluminum Track Curbing

Not To Scale

Sportsfield Specialties Inc 09112026